

YCMC Series Moulded Case Circuit Breaker



YCMC1S-125 3P



YCMC1S-125 4P



YCMC1S-250 4P



YCMC1S-160 4P



YCMC1H-400 3P



YCMC1H-400 4P



YCMC1H-630



YCMC1H-800

DESCRIPTION

Conform To Iec 60947-2

Max: rated Vp Age 500v-50/60hz

Number Of Poles: 3, 4

rated operating voltage (V)

Rated Current:6-800a (1250-1600 Available)

Available As: fixed Type With Front Or Rear Connection,

Withdrawable Type With Front Or Rear Connection

Additional: auxiliary Switch; Shunt Trip Release

Please Contact For Details Infomations

Specification

Model	Breaking capacity Icu (KA)	Rated current In (A)
YCMC-B125	20	16 25 40 63 100 125
YCMC-N125	35	16 25 40 63 100 125
YCMC-S125	50	16 25 40 63 100 125
YCMC-B160	20	25 40 63 100 125 160
YCMC-N160	35	25 40 63 100 125 160
YCMC-S160	50	25 40 63 100 125 160
YCMC-H160	60	25 40 63 100 125 160
YCMC-N250	35	125 160 200 250
YCMC-S250	50	125 160 200 250
YCMC-H250	65	125 160 200 250
YCMC-G250	85	125 160 200 250
YCMC-N400	35	250 320 400
YCMC-S400	50	250 320 400
YCMC-H400	65	250 320 400
YCMC-G400	85	250 320 400
YCMC-N630	35	400 630
YCMC-S630	50	400 630
YCMC-H630	70	400 630
YCMC-G630	85	400 630
YCMC-N800	35	400 630
YCMC-S800	50	400 630
YCMC-H800	70	400 630
YCMC-G800	85	400 630